

EN

## **Compact Pumps**

Hidrostal Screw Centrifugal Compact Pumps are portable, heavy duty field units which combine usability and robustness with the superior hydraulic and solid handling performance of the famous screw centrifugal impeller.



# Compact Pumps - small, portable and ready to use whenever needed.

Hidrostal compact pumps allow non-cloging, trouble-free operation in demanding situations. They are used in slurry and wastewater applications, by emergency management / fire brigades, on construction sites and even in private households.

Hidrostal compact pumps are heavy duty field units which combine usability and robustness with the superior hydraulic and solid handling performance of the famous screw centrifugal impeller. This makes it the preferred pump for all type of municipal and industrial wastewater, slurry and mud but also flood defense applications for portable but also stationary installations.

#### **Typical Applications**

- → Industrial effluent
- → Viscous sludge
- → Return activated sludge
- → Drainage
- → Process waste
- → Sump cleanup
- → Construction sites
- → Flood defense
- → Emergency management/fire brigades

#### **Specifications**

- → Discharge Sizes: 50 80 mm (2 3")
- → Suction Sizes: 50 80 mm (2 3")
- → Head: 0.5 21 m (2 70 ft)
- → Flow: 0.8 25 l/s (12 400 gpm)
- → Power: 0.1 2.4 kW (0.1 3.2 HP)
- → Frequencies: 50 Hz, 60 Hz, VFD
- → Materials: Cast Iron, Ductile Iron, Hi-Chrome, Stainless Steel, Duplex





### **Hidrostal Pumps**

Due to their outstanding characteristics, Hidrostal pumps are used in numerous municipal and industrial sectors all around the world. Our pumps are custom-made and are specially tailored to the needs of each location. Our specialists select the suitable material combinations and individually adapt every pump to the local conditions. We ensure with this process that Hidrostal pumps are successful in difficult applications and achieve the best results with respect to performance, energy efficiency and low life-cycle costs.

- → clog-free pumping
- → high suction capacity
- → gentle delivery due to low shear forces
- → high efficiency
- → stable, steep pump curve
- → long service life
- → low pulsation
- → continous flow proportional to the speed
- → high pressure stability across a wide speed range











Hidrostal Pumps 2225 White Oak Circle Suite 101 Aurora, IL 60502

Phone 630-948-3355

info@hidrostalpumps.com www.hidrostalpumps.com All product and company names are trademarks™ or registered® trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. ©2016 Hidrostal.

